

Product Datasheet

Euroroof RF225 Fibreglass Reinforcement

Sheet No: PD504FR

Issued: June 2012

Pages: 1 of 2

Description

Emulsion bound, chopped strand fibreglass matting.

Use

High grade reinforcement matting is embedded into the Euroroof Impermax QC base coat to strengthen any intricate or project specific areas of detail, providing total reinforcement for all types of substrate overlays within the Euroroof Impermax waterproof membrane.

Application

Embed into the wet Euroroof Impermax QC base coat by roller. Ensure the use of a loaded roller to ensure full saturation of the reinforcement matting.

Fire Rating

Euroroof RF225 fibreglass reinforcement matting is classed as Non-flammable. Packing material is flammable.

Storage

Euroroof RF225 Fibreglass Matting must be stored under cover and in the dry. The rolls are supplied in a plastic film and then in a cardboard box. Do not get the fibreglass wet prior to or during installation.

Product Data

Width	0.94m
Length	110m
Weight	225g/m ²
Weight per roll	26-28kg
Glass fibres	93-96%
Size content	0.35-1.35%
Binder	3-5.4%
Water	0-0.02%

Health & Safety

Material Safety Data Sheets are available upon request, and can also be downloaded directly from www.alumascwaterproofing.co.uk

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Facsimile: +44 (0)1744 648401

Email: waterproofing@alumasc-exteriors.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.