

Product Datasheet

Derbibond NT

Sheet No: PD415FR
Issued: July 2021
Pages: 1 of 1

Description

Derbibond NT is an environmentally friendly one-part, non-toxic, zero VOC, bituminous cold adhesive for flat roofing applications, which remains elastic after application.

Use

For use as a cold adhesive for bonding Derbigum cap sheets in single layer applications, in both new build and refurbishment projects.

Application

Applied by squeegee at the specified coverage rate per m² (usually 1kg/m²). Does not need stirring prior to pouring. Must not be used to seal overlaps, which must be kept free of the adhesive and sealed by gas torch or hot-air welding.

Product Data

Packaging	25 kg drums
Storage	Store in well ventilated area, away from any heat sources
Shelf-life	No expiry date
Flash Point	>200°C
Volatile Organic Compound (VOC) content	zero
Density	1.15 kg/l

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.