

# Product Datasheet

## Alumasc Rubber Mat

Sheet No: PDFR217  
Issued: July 2021  
Pages: 1 of 1

### Description

Alumasc Rubber Mat is a rubber crumb protection mat made from recycled coarse rubber granulate for the temporary or permanent protection of membranes or inverted insulations from potential mechanical damage. The product is water permeable, can be re-used and is also fully recyclable.

It can also be placed beneath rooftop planters and equipment to prevent damage, reduce acoustic transmission and provide anti-vibration properties.

### Installation

The mat is butt jointed and should be laid directly onto the warm roof membrane.

On inverted roofs, the mat would sit on the separator layer over the underlying extruded polystyrene insulation. The mat should be cut so that it extends 50mm in each direction beyond the planter/rooftop equipment it supports.

### Product Data

Roll Width	1250mm
Roll Length	10m
Roll coverage	12.5m <sup>2</sup>
Roll weight	54kg
Product weight	4.38kg/m <sup>2</sup>
Density	730kg/m <sup>3</sup> +/-5%
Thickness	6mm
Dimensional Stability	+/- 1.5%

### Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from [www.alumascroofing.com](http://www.alumascroofing.com).

### Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: [technical@alumascroofing.com](mailto:technical@alumascroofing.com)

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.