

Product Datasheet

Eurorooft PU Insulation Adhesive

Sheet No: PD409FR
Issued: March 2013
Pages: 1 of 1

Description

Eurorooft PU Insulation Adhesive is a solvent free, single component, high foaming polyurethane adhesive.

Use

For bonding rigid insulation boards to a variety of substrates. Metals must be grease and oil free. All substrates must be dust, dirt and debris free.

Application:

Apply in 10mm continuous parallel beads at a rate of 4 beads per metre, at 250mm centres. Around the roof perimeter increase the application to 6 beads per metre, at 175mm centres.

Coverage Rates

Coverage rates will vary depending on substrate conditions. Accurate coverage rates in a given situation should be determined by experiment, however the table below provides some guidance.

Coverage rates	Coverage per 6kg tin
Normal	40-60 m ²
Roof Perimeters	30-40 m ²

Product Data

Packaging	6kg Can
Storage	Store unopened in dry conditions, at temperatures >5°C
Cure Time	Full bond strength achieved within 24 hours.
Shelf-life	6 Months from manufacture, unopened.
Solvents	None
Flash Point	No Flash Point

Health & Safety

Material Safety Data Sheets are available upon request, and can also be downloaded directly from www.alumascroofing.co.uk

Technical Support

Technical advice is available from the Alumasc Technical Services at:

Telephone: +44 (0)1744 648400
Facsimile: +44 (0)1744 648401
Email: roofing@alumasc-exteriors.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.