

Product Datasheet

Euroroof PU Membrane Adhesive

Sheet No: PD408FR
Issued: April 2013
Pages: 1 of 1

Description

Euroroof PU Membrane Adhesive is a single component, low foaming polyurethane adhesive.

Use

For bonding specific membranes to rigid insulation boards. All substrates must be dust, dirt and debris free.

Application:

Apply in 10mm continuous parallel beads at a rate of 4 beads per metre, at 250mm centres. Around the roof perimeter increase the application to 6 beads per metre, at 175mm centres.

Coverage Rates

Coverage rates will vary depending on substrate conditions. Accurate coverage rates in a given situation should be determined by experiment. However the table below provides some guidance. The curing time of the adhesive can be affected by the temperature and relative humidity, however curing will normally begin within 1 hour.

| Coverage rates | Coverage per 6kg tin |
|-----------------|----------------------|
| Normal | 40-60 m ² |
| Roof Perimeters | 30-40 m ² |

Product Data

| | |
|-------------|---|
| Packaging | 6kg Can |
| Storage | Store unopened in dry conditions, at temperatures >5° C |
| Cure Time | 1hour depending on temperature & humidity, full cure within 24 hours. |
| Shelf-life | 6 Months from manufacture, unopened. |
| Solvents | None |
| Flash Point | No Flash Point |

Health & Safety

Material Safety Data Sheets are available upon request, and can also be downloaded directly from www.alumascroofing.co.uk

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400
Facsimile: +44 (0)1744 648401
Email: roofing@alumasc-exteriors.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.