

Product Datasheet

Hydrotech Flex-Flash UN

Sheet No: PD202FR
Issued: July 2018
Pages: 1 of 1

Description

Flex-Flash UN is a thermoset uncured Neoprene rubber, black in colour, with a removable plastic separator film.

Use

For use as a continuous reinforcement in Hydrotech Monolithic Membrane 6125 applications where minor expansion or movement is anticipated, and where Hydrotech is applied over interfaces between different materials.

Application

Fully bonded into the first layer of Hydrotech and gently smoothed in by gloved hand. Flex-Flash UN will stretch whilst warm (i.e. around corners) and will cure in modified shape as it cools. Overlap (also sealed with Hydrotech) 75mm. Second layer of Hydrotech is applied directly to the Flex-Flash UN.

Storage

Store upright in a clean, dry location, away from heat sources.

Product Data

Thickness	1.3mm
Width	150, 300, 450 & 600mm
Length	30.5m
Weight	2.39kg/m ²

Performance Data

Tensile Strength - longitudinal	Min 1305 psi
Tensile Strength - transverse	Min 1305 psi
Elongation at break - longitudinal	>200%
Tear Resistance	Min 150lbs/in
Cold bend	-34° C

Health & Safety

Safety Data Sheets are available upon request, and can also be downloaded directly from www.alumascroofing.co.uk

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.