

Product Datasheet

Hydrotech Flex-Flash F

Sheet No: PD203FR

Issued: May 2012

Pages: 1 of 1

Description

Flex-Flash F is a spunbond polyester fabric, white in colour.

Use

For use as a continuous reinforcement in Hydrotech Monolithic Membrane 6125 applications, where minimal or no expansion or movement is anticipated.

Application

Fully bonded into the first layer of Hydrotech and gently brushed in with a soft broom or brush. Overlap (also sealed with Hydrotech) 75mm. Second layer of Hydrotech is applied directly to the Flex-Flash F.

Storage

Store upright in a clean, dry location, away from heat sources.

Product Data

Thickness	0.5mm
Width	1020mm
Length	200m
Weight	50g/m ²
Weight per roll	10.2kg

Performance Data

Tensile Strength - longitudinal	60N/50mm
Tensile Strength - transverse	60N/50mm
Air permeability	3600l/m ² s (200Pa)

Health & Safety

Material Safety Data Sheets are available upon request, and can also be downloaded directly from www.alumascwaterproofing.co.uk

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Facsimile: +44 (0)1744 648401

Email: waterproofing@alumasc-exteriors.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.