

Product Datasheet

Hydrogard 30

Sheet No: PD207FR

Issued: Jun 2014

Pages: 1 of 1

Description

Hydrogard 30 is glass/polyester reinforced SBS modified bitumen heavy duty protection sheet, with a black mineral surfaced upper side, and polyethylene film on the underside.

Use

As a heavy duty protection sheet for Hydrotech Monolithic Membrane 6125.

Application

Laid directly into the second coat of Hydrotech, with 75mm Hydrotech sealed overlaps.

Storage

Store upright in a clean, dry location, away from heat sources.

Fire Rating

Not applicable - not used in exposed locations.

Product Data

Thickness	4.0mm
Width	1.0m
Length	10m
Weight	4.5 kg/m ²
Weight per roll	45 kg

Performance Data

Tensile Strength - longitudinal	>400 N/50mm
Tensile Strength - transverse	>300 N/50mm
Elongation at break - longitudinal	>35%
Softening point	100°C
Cold Flex	-15°C

Health & Safety

Safety Data Sheets are available upon request, and can also be downloaded directly from www.alumascroofing.co.uk

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: roofing@alumasc-exteriors.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.