

Product Datasheet

Hydrogard 50

Sheet No: PD214FR
Issued: October 2018
Pages: 1 of 1

Description

Hydrogard 50 is a dual glass/polyester reinforced APP modified bitumen extra heavy-duty 5mm protection sheet, with a smooth black finished upper surface, and sanded underside.

Use

As an extra heavy-duty protection sheet for Hydrotech Monolithic Membrane 6125.

Application

Laid directly into the second coat of Hydrotech, with 75mm Hydrotech sealed overlaps.

Storage

Store upright in a clean, dry location, away from heat sources.

Fire Rating

Not applicable - not used in exposed locations.

Product Data

Thickness	5.0mm
Width	1.1m
Length	7.27m
Weight	5.3 kg/m ²
Weight per roll	42kg

Performance Data

Tensile Strength - longitudinal	>1200 N/50mm
Tensile Strength - transverse	>1200 N/50mm
Elongation at break - longitudinal	>50%
Softening point	140°C
Cold Flex	-15°C

Health & Safety

Safety Data Sheets are available upon request, and can also be downloaded directly from www.alumascroofing.co.uk

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400
Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.