

## Product Datasheet Eurorof SA Primer

Sheet No: PD406FR

Issued: August 2017

Pages: 1 of 1

### Description

Eurorof SA Primer is a solvent based primer, black in colour.

### Use

For preparation of new and existing substrates, to maximise the adhesion of the self-adhesive range of Eurorof membranes. Metals must be grease and oil free. All substrates must be dust and debris free. Suitable for horizontal, sloping and vertical surfaces.

### Application:

- Eurorof SA Primer is ready-for-use and must not be thinned or mixed with other products.
- The surfaces to be adhered must be dry and clean.
- The adhesive must only be applied in dry weather conditions at temperatures of at least 5°C, in a thin, even layer, with a brush or roller.
- After an open time of 10 - 15 minutes the glued surfaces must be joined and rolled well.
- It is important to directly position the surfaces correctly because any lateral adjustment is not possible after the first contact.
- Tools can be cleaned with ethyl acetate or white spirit.
- Do not use in conjunction with polystyrene foams.

### Product Data

|             |  |
|-------------|--|
| Packaging   | Drums: 25kg  |
| Storage     | Store in a well-ventilated area, away from heat sources. Keep in airtight drums. |
| Application | Manual Roller or Brush   |
| Flash Point | < 0°C  |
| Shelf-life  | 12 months if stored at a cool temperature in an unopened drum.                   |
| Coverage    | 100 - 200g/m <sup>2</sup> (100 - 250m <sup>2</sup> per drum)                     |

### Health & Safety

Safety Data Sheets are available upon request, and can also be downloaded directly from [www.alumascroofing.co.uk](http://www.alumascroofing.co.uk)

### Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: [technical@alumascroofing.com](mailto:technical@alumascroofing.com)

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.