

# Product Data Sheet

## CaltechQC Cleaner

Sheet No: CQCC1

Issued: January 2017

Pages: 1 of 1

### Description

CaltechQC Cleaner is a cleaner for all CaltechQC PMMA products.

### Use

For use as a cleaner to pre-treat substrates, reactivate transition areas, degrease metals, clean substrates and clean tools.

### Application: Cleaning substrates and reactivating transition areas

- Apply using a small Alumasc Cleaning Rag, cloth or mop.
  1. Wearing suitable gloves, apply a thin layer of CaltechQC Cleaner using a clean Alumasc Cleaning Rag, cloth or mop, wiping to remove excess CaltechQC Cleaner and contamination.
  2. Overlay after CaltechQC Cleaner has evaporated and minimum 20 minutes / maximum 60 minutes after application.

### Application: Tool cleaning

- Clean tools with CaltechQC Cleaner immediately after use. Placing tools in Alumasc Cleaner will not prevent hardening.
- Where resin has cured on the tools and the tool is solvent resistant, leave the tool submerged in Alumasc Cleaner in a sealed container to minimise evaporation until the resin can be removed.

### Application: Adhesion testing / dolly cleaning

- Submerge the dollies in CaltechQC Cleaner in a sealed container to minimise evaporation until the adhesive and resins can be removed.

### Note

Always keep the lids of containers of CaltechQC Cleaner tightly sealed to avoid evaporation.

### Product Data

Packaging	Resin: 9L canisters / 27L canisters
Colours	Transparent
Coverage	0.20L/m <sup>2</sup> depending on the degree of soiling and type of substrate
Application	Alumasc Cleaning Rag / cloth / mop
Evaporation time	Approximately 20 minutes
Storage	Should be stored unopened in a cool, dry, well ventilated place above freezing and out of direct sunlight in the original container. If the contents have been opened, re-seal ensuring the lid is air tight. Avoid direct sunlight on site.
Shelf-life	For at least 6 months if stored as above

### Health & Safety

Material Safety Data Sheets are available upon request, and can also be downloaded directly from [www.alumascroofing.co.uk](http://www.alumascroofing.co.uk)

### Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Facsimile: +44 (0)1744 648401

Email: [roofing@alumasc-exteriors.co.uk](mailto:roofing@alumasc-exteriors.co.uk)