

LIGHTWEIGHT CRUSHED BRICK BLEND.

DESCRIPTION:

A blend of graded (0-15mm) crushed brick and clay aggregate to produce a lightweight infill or drainage layer. The brick is a recycled material responsibly sourced from within the United Kingdom.

Loose Bulk Density: 1000 Kg/m³ (approximate)

Saturated Density: Approx. 1200 kg/m³

pH Value: 6.5 – 7.5

Available in: Plastic sacks on pallets
Bulk bags

SAFETY DATA

In the condition sold, the product does not present a hazard to health. The products are not required to carry a hazard label under the chemicals (Hazard information and packaging for supply) Regulations 1994 (CHIP 2). When chipped, brick particles can cause damage to the eyes. Eye protection to B.S. EN 166 should be worn.

When products are mechanically crushed, respirable dust will be produced which can contain silica (quartz). Engineering control measures should be employed to keep airborne dust to a minimum. If adequate local exhaust ventilation equipment is not provided, dust masks, or their equivalent, to type FFP2 should be worn.

FIRE

There are no direct risks of fire or explosion from this product.

OFF-LOADING

Ensure that the lifting equipment is suitable and will carry the weight.

FIRST AID

Where particles enter the eye, irrigate well with copious amounts of clean water. Seek medical attention, if necessary.

Inhalation of dust, remove to fresh air and seek medical attention, if necessary.

DISPOSAL

Waste from clay brick is easy to handle, non-toxic and inert. However, its storage and disposal should be carried out in accordance with section 34 of the Environmental Protection Act: Waste Management – The Duty of Care.



*This information is offered for guidance purposes only.
No warranty is implied or given.*