

Product Datasheet Eurorooof SB Primer

Sheet No: PD035FR
Issued: June 2017
Pages: 1 of 1

Description

Eurorooof SB Primer is a solvent based primer for bituminous waterproofing systems.

The product is supplied in 25L drums and is simply brush or roller applied straight from the drum to the substrate. The benefit of a solvent based primer is that it is fast curing and provides good penetration into the substrate thereby resulting in an excellent surface for the subsequent waterproofing build up.

- Propellant free packaging, simple disposal
- Coloured black
- Unaffected by rain, frost or fog immediately after application



Method of Use

The primer is supplied in 25L drums but can be packaged to customer's specific requirements

1. Ensure the substrate is dry do not apply if there is any standing water or condensation, take care to ensure porous substrates prone to high moisture content are completely dry prior to application and free from loose and foreign material, oil/grease and other contaminates.
2. Ambient and substrate temperatures must be at minimum 5°C.
3. Remove the lid from the packaging then stir the primer thoroughly before and during use.
4. Apply the primer to the deck substrate with a brush or roller.
5. Allow the primer to dry to touch before applying subsequent layers.
6. Curing time can differ and is dependent on the ambient weather conditions such as temperature and humidity.

Technical Data

Chemical base	Bitumen
Viscosity	Kinematic at 20°C - 11mm ² /s
Specific Gravity	1.0 - 1.10 at 20°C
Solids Content	40 - 50%
Flammability	Flash point: 35°C
Colour	Black
Chemical Resistance	Resistant to water, dilute acids, alkalis, and aliphatic oils.
Service Temperature	-20°C to +100°C
Application Temperature	5°C - 25°C
Coverage per litre	7 - 10m ² (dependent on substrate)
Storage temperature	4°C - 25°C. Lower temperatures can cause permanent damage to the product
Cleaner	White Spirit

Health & Safety

Safety Data Sheets are available upon request, and can also be downloaded directly from:
www.alumascroofing.co.uk

Technical Support

Technical advice is available from the Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: roofing@alumasc-exteriors.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.

ALUMASC EXTERIOR BUILDING PRODUCTS LTD

Tel: +44 (0)1744 648400

Email: roofing@alumasc-exteriors.co.uk www.alumascroofing.co.uk