

Product Datasheet Alumasc Thinner

Sheet No: PD420FR
Issued: January 2018
Pages: 1 of 1

Description

Alumasc Thinner is a single component solvent, brown/black in colour.

Uses

For the dilution of Alumasc products strictly as directed on product data sheets, and also for the cleaning of tools. Do not use for the cleaning of decorative or exposed surfaces - may cause staining.

Storage and Transport

- Flammable/combustible - Keep away from oxidisers, heat and flames.
- Store in tightly closed original container in a dry, cool and well-ventilated place.
- Keep in original container.
- Avoid contact with oxidising agents.
- Storage class: Flammable liquid storage.
- The storage and conditions must meet the statutory requirements of The Highly Flammable Liquids and Petroleum Gases Regulations 1972.
- Transport class: UN1993

Product Data

Drum size	5 l
Colour	Brown/black
Flash Point	35-47 ° C
Solids Content	n/a
Density	0.79 kg/l
Shelf life	2 years in unopened drums

Health and Safety

- Safety Datasheets can be downloaded directly from www.alumascroofing.co.uk

Technical Support

- Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: roofing@alumasc-exteriors.co.uk

NB: Current versions of Alumasc Product Datasheets can be downloaded directly from:
www.alumascroofing.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.