

Product Datasheet Caltech Butyl Strip

Sheet No: PD544FR

Issued: January 2018

Pages: 1 of 1

Description

Caltech Butyl Strip has been developed specifically for adherence to all difficult porous or non-porous surfaces. These tapes are laminated with non-woven fleece backing ideal for subsequently applying liquid waterproofing systems. The adhesive surface is protected by silicone coated release liner with finger lift edges for easy backing removal. The sealing compound is manufactured from a synthetic rubber based formula with exceptionally high surface adherence.

Use

Caltech Butyl Strip is suitable for applications such as waterproofing of roofs, concrete perimeters such as in basements, garages & terraces as well as joints and seams found on building & roofing surfaces. Its main applications are to be used as a jointing tape for sealing joints insulation boards, outlets and detail work, to which a liquid waterproofing system can be subsequently applied. This removes the need for embedding fleece in liquid resins for sealing these areas, making it more economical and decreasing application times.

Caltech Butyl Strip is also the ideal product for cut edge corrosion work on sheet metal roofing, a much more efficient application method reducing labour times prior to application of liquids. The strip seals and waterproofs the exposed cut edge and also is suited for sealing joints between sheets ensuring a watertight and aesthetically pleasing finish once the liquid coating has been applied. Surfaces to receive the product must be clean and free from contamination.

- Long-term resistant
- Solvent free
- Shrinkage free
- Free of abrasive fillers
- Excellent resistance to water & water vapour
- Excellent adhesion to almost all substrates
- Odour free at room temperature
- Easy application

Storage and Transport

Store in original packaging in a location away from sources of heat or ignition, dampness and extremes of temperature. Keep protected from rain and sunlight.

Product Data

Roll size	25mm x 100m
Colour	White
Shelf life	Use within 12 months of purchase

Health and Safety Safety Data Sheets can be downloaded directly from www.alumascroofing.co.uk

Technical Support Technical advice is available from Alumasc Technical Services at:

Tel: +44 (0)1744 648400 Email: roofing@alumasc-exteriors.co.uk

NB: Current versions of Euroroof Caltech Product Datasheets can be downloaded directly from: www.alumascroofing.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.