

Product Data Sheet

Caltech QC Quartz

Sheet No: PDFR720
Issued: July 2021
Pages: 1 of 1

Use

Light coloured, naturally rounded aggregate used in Alumasc systems to provide a hard-wearing anti-skid finish, as a key in primers and as a bulk filler.

Properties

- Hard wearing
- Washed, dried & dedusted
- Subject to electro-magnetic separation to minimise FE content
- Specific gravity g/cm³ approx. 2.7⁽¹⁾
- Hardness (Mohs) approx. 7.2⁽¹⁾
- Polished stone value (PSV) approx. 57⁽¹⁾

⁽¹⁾As a natural product the figures provided are indicative only and do not constitute a specification.

Components

Component	Product
Aggregate	Caltech QC Quartz

Packaging

Component	Product
Caltech QC Quartz 0.3-0.6mm	25.00 kg
Caltech QC Quartz 0.4-0.8mm	25.00 kg
Caltech QC Quartz 0.4-1.2mm	25.00 kg
Caltech QC Quartz 0.7-1.2mm	25.00 kg

Colours

Buff/Grey.

Consumption

Refer to Alumasc specification.

Storage

Store in a dry area.

Disposal information

Refer to Safety Data Sheets (see below).

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.